



Product Data Sheet

PORON® AquaPro® 4701-37TS9-19

Product Function - Water Sealing
Self-Adhesive

| PROPERTY | TEST METHOD | VALUE |
|---|---|--------------------------------|
| PHYSICAL | | |
| Density, kg/m ³ (lb./ft ³) | ASTM D 3574-95, Test A | 304 (19) |
| Tolerance, % | | ± 15 |
| Thickness, Foam+PET+Adhesive, mm (inches) | Digital Tester (ONO SOKKI) | 0.30 - 0.50 (0.012 - 0.020) |
| Tolerance, % | | ± 20 |
| Standard Color (Code) | | Black (04) |
| Shelf Life, months | *From date of manufacture | 12 |
| Peel Adhesion, gf/in | ASTM D 1000 180° Peel | ≥800 |
| Compression Force Deflection, kPa (psi) | Modified ASTM D3574: PTP-0033 @ 25% deflection | 41.3 - 110.2 (6 - 16) |

* Storage in the original packaging located in a dry cool environment is recommended.

3. Product Structure

Structure:



①
②
③
④

Description

| | |
|---|-----------------|
| ① | PU Foam |
| ② | Transparent PET |
| ③ | Adhesive |
| ④ | Release PET |

Notes:

- All metric conversions are approximate.
- Additional technical information is available.
- Typical values should not be used for specification limits.



120 Seegers Ave, Elk Grove Village, IL 60007

Phone: 847.593.5630

srpco.com

info@srpco.com



The information contained in this Data Sheet is intended to assist you in designing with Rogers' Elastomeric Material Solutions. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Data Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of PORON Polyurethane Foam Materials for each application. The Rogers logo, PORON, AquaPro and the PORON logo are trademarks of Rogers Corporation or one of its subsidiaries. © 2025 Rogers Corporation. All rights reserved. 0825-PDF • Publication #17-452PC www.rogerscorp.com