

PORON® 4790-79RL-15 Series-04PBLK

Display Back Pad-PET Self-Adhesive

| PROPERTY | | TEST METHOD | TYPICAL VALUE | |
|--------------------|---|---|--------------------|------------|
| FOAM | PHYSICAL | | 79RL-15006 | 79RL-15008 |
| | Density, kg/m ³ (lb./ft ³) | ASTM D3574-95, Test A | 240 (15) | |
| | Tolerance, % | | ±10 | |
| | Thickness, Foam & FAL, mm (inches) | ASTM D3574-95, Test A | 0.15 | 0.20 |
| | Tolerance, % | | (0.006) | (0.008) |
| | Standard Color (Code) | | Black (04) | |
| | Compression Force Deflection, kPa (psi) | 0.51 cm/min (0.2"/min) Strain Rate Force measured @ 25% Deflection | 13.7~41.3 (1~6) | |
| Shelf Life, months | From date of manufacture | 12 | | |

With the exception of the thickness measurement, the data mentioned above represents results of testing the PORON® polyurethane foam only. This product is supported on a 0.05 mm (2-mil) release polyester film (PET).

Notes:

- All metric conversions are approximate.
- Additional technical information is available.
- Typical values should not be used for specification limits.

For more information and to request a sample, please contact our team of experts at solutions@rogerscorp.com